

- Amazing power and versatility in a very compact package
- ✓ Wide range of attachments available for year-round use



1910 mm



700 kg

Avant 200 series is an amazingly powerful and versatile compact loader considering its small size. The basic articulated design and hydraulic 4x4 transmission is the same as in bigger Avants.

Easy access to driver's seat, ample space for operator, logical and easy-to-use controls and excellent visibility to the working area guarantee efficient operation. Avant quick attach system for attachments and hydraulic multi connector are standard features as well.

Avant 200 series is very easy to operate. Its compact size and maneuverability enable endless possibilities in small spaces, for instance on the yard and in the garden. Since the loader is easy to transport on a trailer, you can effortlessly relocate it wherever it is needed.

The wide Avant attachment range allows working all year round – be it earthmoving, lawn mowing, digging, load handling, snow removal etc. 200 series is much more than a ride-on lawn mower, compact tractor or a quad bike.



1400 mm



350 kg



15-19 kW / 20-25 hp gasoline



0 - 10 km/h

## specifications





## **Machine width**

| Wheel size      | Profile     | Width   |
|-----------------|-------------|---------|
| 20 x 8.00 - 10  | TR or grass | 995 mm  |
| 20 x 8.00 - 10* | TR or grass | 1025 mm |

\*) With spacers

| Model                                       | AVANT 220                | AVANT 225                              |
|---|--------------------------|--|
| Engine                                      | Kohler CV640 Stage V     | Kohler ECV730 EFI Stage V              |
| Function                                    | 4-stroke                 | 4-stroke,<br>Electronic Fuel Injection |
| Fuel  | gasoline                 | gasoline                               |
| Engine output (ECE R120)                    | 14,9 kW (20 hp)          | 18,6 kW (25 hp)                        |
| Auxiliary hydraulics                        |                          |  |
| <ul> <li>Front outlet (standard)</li> </ul> | 30 l/min                 | 42 l/min                               |
| <ul> <li>Rear outlet (optional)</li> </ul>  | 7 l/min                  | 7 l/min                                |
| Drive speed                                 | 0 - 10 km/h              | 0 - 10 km/h                            |
| Wheels                                      | 20x8.00-10 tractor/grass | 20x8.00-10 tractor/grass               |
| Pulling force                               | 620 daN                  | 640 daN                                |
| Tipping load                                | 350 kg                   | 350 kg                                 |
| Lifting height                              | 1400 mm                  | 1400 mm                                |
| Weight                                      | 700 kg                   | 700 kg                                 |
| Height                                      | 1880 mm                  | 1880 mm                                |
| Width                                       | 995/1025 mm              | 995/1025 mm                            |
| Length                                      | 1910 mm                  | 1910 mm                                |
|   |                          |  |